

(43) Date of publication:
03.01.2001 Bulletin 2001/01

(51) Int. Cl.⁷: **B65D 41/04**

(21) Application number: 00304931.9

(22) Date of filing: 09.06.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 01.07.1999 GB 9915273

(71) Applicant:
DRAGON PLASTICS LIMITED
Pontypridd, Mid Glamorgan CF37 5TF (GB)

(72) Inventor: **Walding, Dean**
Treharris, Mid-Glamorgan CF46 5HQ (GB)

(74) Representative:
Chettle, Adrian John et al
Withers & Rogers,
Goldings House,
2 Hays Lane
London SE1 2HW (GB)

(54) Moulded closure and method of manufacture

(57) A moulded closure for a container has a seal (41) moulded through the wall of a screw threaded cap (10). The seal material may extend over the outer surface of the cap to enhance grippability thereof. A moulding method includes backing-off an inner mould part (21) to define a seal cavity (31), after the cap has been moulded.



Description

[0001] This invention concerns a closure of moulded plastic, and more particularly a closure having an integral moulded seal.

[0002] Plastic screw closures of e.g. polypropylene are well known. It is sometimes necessary to provide a seal between the closure and the container to which it is to be fitted, for example to prevent leakage of liquid. Such a seal is usually inserted into the closure after moulding, and thus requires separate manufacturing and assembly steps. Occasionally a separate seal may not seat in the closure or on the container, and this may result in leakage of the contents of the container.

[0003] What is required is a seal that does not require a separate assembly step, that is inexpensive, reliable and easily manufactured, and is generally more precise.

[0004] According to the invention there is provided a moulded plastics closure for a container, the closure comprising a cap having an end wall and a skirt, and a seal moulded therein through an aperture in said cap. Preferably the aperture is in the end wall. In a preferred embodiment said aperture is substantially annular.

[0005] Such a closure can be injection moulded in two stages, a suitable material for the seal being injected immediately after the material of the cap. Typically the cap is moulded of polypropylene whereas the seal is moulded of a relatively soft elastomer such as TPE (tetraphenylethylene).

[0006] Moulding of the seal through the end wall is especially advantageous if the seal moulding cavity is formed by backing-off the part of the mould which defines the cap interior, the feed channel for the seal being defined by a removable outer mould part.

[0007] In a preferred embodiment the exterior of the cap is overmoulded with the material of the seal. Such an overmoulding results in a soft grippable closure which is especially useful for containers which may in use become wet, for example containers for shampoo or shower gel. A soft overmoulding also improves grippability on tightly secured closures.

[0008] The overmoulding may encompass the entire outer surface of the end wall and skirt, or only part thereof. Where the end wall aperture is substantially annular, the overmoulding may be coincident with this aperture. Such a two component closure can be designed to be distinctive and colourful. The overmoulding may increase the outside diameter of the cap to enhance grippability thereof.

[0009] The invention also provides a method of injection moulding a plastics closure, the method comprising:

moulding a cap having an aperture in the wall thereof;

substituting an outer mould to define an injection path through said aperture;

backing-off an inner mould part to define a seal cavity; and

moulding a seal through said injection path.

5 [0010] Preferably the aperture is defined in the end wall, and the cap is moulded on an injection moulding machine having a pivotable platten, the outer mould part being substituted as the inner mould part and freshly moulded cap pivots from the first to the second moulding position.

10 [0011] Preferably the cap is a screw cap, and the inner mould part unscrews to define the seal cavity.

[0012] Other features of the invention will be apparent from the following description of two preferred embodiments shown by way of example only in the accompanying drawings in which:-

Fig. 1 is an axial section through a cap forming part of a closure of the invention;

Fig. 2 is a partial axial section through a primary mould for the closure of Fig. 1; and

Fig. 3 is a partial axial section through a secondary mould corresponding to Fig. 2.

[0013] Although the invention has been described in relation to a screw-threaded closure, it is equally applicable to other kinds of closure, for example those which rely on snap-fitting or are hinged.

[0014] With reference to Fig. 1, a cap 10 of e.g. polypropylene comprises an end wall 11 and a skirt 12 having an internal thread 13. An annular channel 14 is defined in the end wall, the inner side of the channel being linked to the outer side by spokes 15. The channel 14 extends axially of the cap and is defined by annular walls 16,17. Axially extending ribs 18 are provided on the upper part of the skirt as illustrated.

[0015] Fig. 2 shows an injection mould for the cap comprises a core 21, a skirt mould 22 and an end wall mould 23. Representative split lines 25,26 between the respective mould parts are indicated, but the skilled man will choose an appropriate design to suit the configuration of the cap. Feed channels for the injection moulding material are not shown, but can be provided in any suitable location.

[0016] After moulding of the cap, the core 21 is unscrewed in order to define a seal cavity 31 (Fig. 3). The annular walls 16,17 permit axial core movement and thus definition of the inner and outer circumferential walls of the seal. Cavities 32,33 (and others not shown) are also formed, but are enclosed and have no function.

[0017] The outer mould is removed, and replaced by a secondary outer mould 24. The channels 14 are clear apart from the spokes 15, and an overmoulding cavity 34 is defined over the end wall, as illustrated. The overmoulding/seal material is then injected through the outer mould 24 thus forming at the same time a seal and

a grippable annulus on the cap.

[0018] The closure is then removed from the mould conventionally. The overmoulding adheres to the cap and is further secured against relative rotation by the spokes 15.

[0019] The overmoulding may of course cover the entire surface of the end wall 11, and/or may extend radially outwardly to form a mushroom like head, the increased diameter of which may enhanced grippability.

[0020] A typical moulded closure is illustrated in Fig. 4. The annular seal 41 is complete notwithstanding the spokes 15. Additional rotational security of the overmoulding is provided by the ribs 18. The overmoulding 42 defines a relatively soft grippable surface.

[0021] The core 21 may comprise co-axial parts consisting of a central stationary component defining the wall 16 and an outer cylindrical part defining the thread 13, and relatively rotatable with respect to the inner stationary component. Such an arrangement allows cogs of the inner component to engage the wall 16 and thereby prevent relative rotation of the cap as the outer cylindrical part unscrews to define the seal cavity 31.

[0022] Although the seal cavity extends across the underside of walls 16,17, it need not do so provided the mouth of the container is precisely aligned with the channel 14.

Claims

1. A moulded plastics closure for a container, the closure comprising a cap (10) having an end wall (11) and a skirt (12), and a seal (41) moulded therein through an aperture (14) in said cap.

2. A closure according to claim 1 wherein said aperture (14) is in the end wall (11).

3. A closure according to claim 2 wherein said aperture (14) is substantially annular.

4. A closure according to any preceding claim wherein the exterior of said cap (10) is overmoulded with the material of said seal (41).

5. A closure according to claim 4 wherein said overmoulding encompasses the entire outer surface of said end wall (11) and skirt (12).

6. A closure according to claim 5 wherein said cap includes protrusions (18) on the exterior thereof to engage said overmoulding.

7. A closure according to any preceding claim wherein the material of said cap (10) and the material of said seal (14) are of different colours.

8. A method of injection moulding a plastics closure,

the method comprising:

moulding a cap having an aperture in the wall thereof;
substituting an outer mould part to define an injection path through said aperture;
backing-off an inner mould part to define a seal cavity; and
moulding a seal through said injection path.

9. A method according to claim 8 wherein an injection moulding machine has a pivotable platten, the outer mould part being substituted as the inner mould part and freshly moulded cap pivots from a first to a second moulding position.

10. A method according to claim 8 or claim 9 wherein said inner mould part unscrews to define the seal cavity.






Fig 1








Fig 4



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 065 149 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
04.02.2004 Bulletin 2004/06

(51) Int Cl.7: **B65D 41/04, B29C 45/16**

(43) Date of publication A2:
03.01.2001 Bulletin 2001/01

(21) Application number: **00304931.9**

(22) Date of filing: **09.06.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Walding, Dean**
Treharris, Mid-Glamorgan CF46 5HQ (GB)

(30) Priority: **01.07.1999 GB 9915273**

(74) Representative: **Chettle, Adrian John et al**
Withers & Rogers,
Goldings House,
2 Hays Lane
London SE1 2HW (GB)

(71) Applicant: **DRAGON PLASTICS LIMITED**
Pontypridd, Mid Glamorgan CF37 5TF (GB)

(54) **Moulded closure and method of manufacture**

(57) A moulded closure for a container has a seal
(41) moulded through the wall of a screw threaded cap
(10). The seal material may extend over the outer sur-

face of the cap to enhance grippability thereof. A mould-
ing method includes backing-off an inner mould part (21)
to define a seal cavity (31), after the cap has been
moulded.




Fig 4

EP 1 065 149 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 4931

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	FR 2 759 351 A (AXIA CAP) 14 August 1998 (1998-08-14)	1-4,7	B65D41/04 B29C45/16
Y	* page 2, line 6-36 *	5,6	
A	* figures 1-4 *	8	

X	US 4 754 892 A (RETIEF CHARLES T) 5 July 1988 (1988-07-05)	1-4	
A	* column 2, line 22-58 *	8,10	
	* figures 1-4 *		

X	DE 195 08 509 A (SOOTH JUERGEN) 12 September 1996 (1996-09-12)	1-4,7	
A	* column 3, line 35 - column 4, line 1 *	8	
	* column 5, line 12-55 *		
	* figures 1-6 *		

Y	US 4 627 548 A (THOMPSON KENNETH H) 9 December 1986 (1986-12-09)	5,6	
	* column 1, line 48-50 *		
	* column 3, line 4-30 *		
	* figures 1-3 *		

X	US 5 439 124 A (MOCK ELMAR) 8 August 1995 (1995-08-08)	8-10	B65D B29C
	* column 9, line 52-59 *		
	* column 11, line 37 - column 12, line 18 *		
	* column 12, line 42-63 *		
	* figures 3,4,5A-5H,6 *		

A	US 2 074 830 A (CONNER BENJAMIN F) 23 March 1937 (1937-03-23)	5,6	
	* page 1, column 1, line 3,4 *		
	* page 1, column 2, line 11-20 *		
	* figures 1-6 *		

The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
MUNICH		26 November 2003	Rodriguez Gombau, F
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (3.82) (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 4931

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-11-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2759351	A	14-08-1998	FR 2759351 A1	14-08-1998
			AT 236055 T	15-04-2003
			AU 3037297 A	05-01-1998
			BR 9702273 A	02-05-2000
			CA 2224472 A1	04-12-1997
			DE 69720396 D1	08-05-2003
			DE 69720396 T2	30-10-2003
			EP 0851831 A1	08-07-1998
			WO 9745330 A1	04-12-1997
			JP 11509819 T	31-08-1999
			US 5975354 A	02-11-1999
US 4754892	A	05-07-1988	AU 6757187 A	23-07-1987
			BR 8700368 A	08-12-1987
			DE 3701197 A1	30-07-1987
			ES 2005855 A6	01-04-1989
			FR 2593148 A1	24-07-1987
			GB 2190902 A ,B	02-12-1987
			IT 1210553 B	14-09-1989
			JP 62182059 A	10-08-1987
			ZA 8700135 A	26-08-1987
DE 19508509	A	12-09-1996	DE 19508509 A1	12-09-1996
US 4627548	A	09-12-1986	NONE	
US 5439124	A	08-08-1995	AT 148389 T	15-02-1997
			AU 663887 B2	26-10-1995
			AU 2509792 A	27-04-1993
			CA 2095943 A1	18-03-1993
			WO 9305945 A1	01-04-1993
			DE 59207993 D1	13-03-1997
			EP 0557487 A1	01-09-1993
			ES 2101115 T3	01-07-1997
			JP 5213349 A	24-08-1993
			KR 214739 B1	02-08-1999
			MX 9205268 A1	01-05-1993
			NO 931769 A	14-05-1993
			JP 5213341 A	24-08-1993
US 2074830	A	23-03-1937	NONE	

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82